

Practitioner's Docket No. 915.401

CHAPTER II

Preliminary Classification:

Proposed Class:

Subclass:

NOTE: "All applicants are requested to include a preliminary classification on newly filed patent applications. The preliminary classification, preferably class and subclass designations, should be identified in the upper right-hand corner of the letter of transmittal accompanying the application papers, for example 'Proposed Class 2, subclass 129.' " M.P.E.P., § 601, 7th ed.

TRANSMITTAL LETTER
TO THE UNITED STATES ELECTED OFFICE (EO/US)

(ENTRY INTO U.S. NATIONAL PHASE UNDER CHAPTER II)

PCT/IB00/00706 8 May 2000 10 May 1999
INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PRIORITY DATE CLAIMED

Header Compression
TITLE OF INVENTION

Martin BERGENWALL AND Patrick FLYKT
APPLICANT(S)

Box PCT
Assistant Commissioner for Patents
Washington D.C. 20231
ATTENTION: EO/US

CERTIFICATION UNDER 37 C.F.R. § 1.10*
(Express Mail label number is mandatory.)
(Express Mail certification is optional.)

I hereby certify that this Transmittal Letter and the papers indicated as being transmitted therewith is being deposited with the United States Postal Service on this date November 9, 2001, in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EV005523171, addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231.

Judith Schick

(type or print name of person mailing paper)

Judith Schick

Signature of person mailing paper

WARNING: Certificate of mailing (first class) or facsimile transmission procedures of 37 C.F.R. § 1.8 cannot be used to obtain a date of mailing or transmission for this correspondence.

***WARNING:** Each paper or fee filed by "Express Mail" **must** have the number of the "Express Mail" mailing label placed thereon prior to mailing. 37 C.F.R. § 1.10(b).
"Since the filing of correspondence under § 1.10 without the Express Mail mailing label thereon is an oversight that can be avoided by the exercise of reasonable care, requests for waiver of this requirement will **not** be granted on petition." Notice of Oct. 24, 1996, 60 Fed. Reg. 56,439, at 56,442.

(Transmittal Letter to the United States Elected Office (EO/US) [13-18]—page 1 of 8)

10030749-04002

10/030749

NOTE: To avoid abandonment of the application, the applicant shall furnish to the USPTO, not later than 20 months from the priority date: (1) a copy of the international application, unless it has been previously communicated by the International Bureau or unless it was originally filed in the USPTO; and (2) the basic national fee (see 37 C.F.R. § 1.492(a)). The 30-month time limit may not be extended. 37 C.F.R. § 1.495.

531 Rec'd PCT

09 NOV 2001

WARNING: Where the items are those which can be submitted to complete the entry of the international application into the national phase are subsequent to 30 months from the priority date the application is still considered to be in the international state and if mailing procedures are utilized to obtain a date the express mail procedure of 37 C.F.R. § 1.10 must be used (since international application papers are not covered by an ordinary certificate of mailing—See 37 C.F.R. § 1.8.

NOTE: Documents and fees must be clearly identified as a submission to enter the national state under 35 U.S.C. § 371 otherwise the submission will be considered as being made under 35 U.S.C. § 111. 37 C.F.R. § 1.494(f).

- I. Applicant herewith submits to the United States Elected Office (EO/US) the following items under 35 U.S.C. § 371:
- ☒ This express request to immediately begin national examination procedures (35 U.S.C. § 371(f)).
 - ☒ The U.S. National Fee (35 U.S.C. § 371(c)(1)) and other fees (37 C.F.R. § 1.492) as indicated below:

10/030749

2. Fees

531 Rec'd PCT/F

09 NOV 2001

CLAIMS FEE	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
<input checked="" type="checkbox"/>	TOTAL CLAIMS	15 - 20 =	0		
	INDEPENDENT CLAIMS	2 - 3 =	0		
	MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ 280.00
BASIC FEE**	<input type="checkbox"/> U.S. PTO WAS INTERNATIONAL PRELIMINARY EXAMINATION AUTHORITY Where an International preliminary examination fee as set forth in § 1.482 has been paid on the international application to the U.S. PTO: <input type="checkbox"/> and the international preliminary examination report states that the criteria of novelty, inventive step (non-obviousness) and industrial activity, as defined in PCT Article 33(1) to (4) have been satisfied for all the claims presented in the application entering the national stage (37 C.F.R. § 1.492(a)(4)) 100 <input type="checkbox"/> and the above requirements are not met (37 C.F.R. § 1.492(a)(1)) 710				
	<input checked="" type="checkbox"/> U.S. PTO WAS NOT INTERNATIONAL PRELIMINARY EXAMINATION AUTHORITY Where no international preliminary examination fee as set forth in § 1.482 has been paid to the U.S. PTO, and payment of an international search fee as set forth in § 1.445(a)(2) to the U.S. PTO: <input type="checkbox"/> has been paid (37 C.F.R. § 1.492(a)(2)) 740 <input type="checkbox"/> has not been paid (37 C.F.R. § 1.492(a)(3)) 1040 <input checked="" type="checkbox"/> where a search report on the international application has been prepared by the European Patent Office or the Japanese Patent Office (37 C.F.R. § 1.492(a)(5)) 890				
	Total of above Calculations =				
	890.00				
SMALL ENTITY	Reduction by 1/2 for filing by small entity, if applicable. Affidavit must be filed also. (note 37 C.F.R. § 1.9, 1.27, 1.28)				
	Subtotal				
	Total National Fee \$				
	890.00				
	Fee for recording the enclosed assignment document \$40.00 (37 C.F.R. § 1.21(h)). (See Item 13 below). See attached "ASSIGNMENT COVER SHEET".				
TOTAL	Total Fees enclosed \$ 890.00				

10/030749

09 NOV 2001

*See attached Preliminary Amendment Reducing the Number of Claims.

- i. ☒ A check in the amount of \$890.00 to cover the above fees is enclosed.
- ii. ☐ Please charge Account No. _____ in the amount of \$ _____.
A duplicate copy of this sheet is enclosed.

****WARNING:** "To avoid abandonment of the application the applicant shall furnish to the United States Patent and Trademark Office not later than the expiration of 30 months from the priority date: * * * (2) the basic national fee (see § 1.492(a)). The 30-month time limit may not be extended." 37 C.F.R. § 1.495(b).

WARNING: If the translation of the international application and/or the oath or declaration have not been submitted by the applicant within thirty (30) months from the priority date, such requirements may be met within a time period set by the Office. 37 C.F.R. § 1.495(b)(2). The payment of the surcharge set forth in § 1.492(e) is required as a condition for accepting the oath or declaration later than thirty (30) months after the priority date. The payment of the processing fee set forth in § 1.492(f) is required for acceptance of an English translation later than thirty (30) months after the priority date. Failure to comply with these requirements will result in abandonment of the application. The provisions of § 1.136 apply to the period which is set. Notice of Jan. 3, 1993, 1147 O.G. 29 to 40.

3. ☒ A copy of the International application as filed (35 U.S.C. § 371(c)(2)):

NOTE: Section 1.495 (b) was amended to require that the basic national fee and a copy of the international application must be filed with the Office by 30 months from the priority date to avoid abandonment. "The International Bureau normally provides the copy of the international application to the Office in accordance with PCT Article 20. At the same time, the International Bureau notifies applicant of the communication to the Office. In accordance with PCT Rule 47.1, that notice shall be accepted by all designated offices as conclusive evidence that the communication has duly taken place. Thus, if the applicant desires to enter the national stage, the applicant normally need only check to be sure the notice from the International Bureau has been received and then pay the basic national fee by 30 months from the priority date." Notice of Jan. 7, 1993, 1147 O.G. 29 to 40, at 35-36. See item 14c below.

- a. ☐ is transmitted herewith.
- b. ☐ is not required, as the application was filed with the United States Receiving Office.
- c. ☒ has been transmitted
- i. ☒ by the International Bureau.
Date of mailing of the application (from form PCT/1B/308): 16 Nov., 2000
- ii. ☐ by applicant on _____
Date

4. ☒ A translation of the International application into the English language (35 U.S.C. § 371(c)(2)):

- a. ☐ is transmitted herewith.
- ✓ b. ☒ is not required as the application was filed in English.
- c. ☐ was previously transmitted by applicant on _____
Date
- d. ☐ will follow.

10030749-042902

10/030749
531 Rec'd PCT/PT 09 NOV 2001

5. ☐ Amendments to the claims of the International application under PCT Article 19 (35 U.S.C. § 371(c)(3)):

NOTE: The Notice of January 7, 1993 points out that 37 C.F.R. § 1.495(a) was amended to clarify the existing and continuing practice that PCT Article 19 amendments must be submitted by 30 months from the priority date and this deadline may not be extended. The Notice further advises that: "The failure to do so will not result in loss of the subject matter of the PCT Article 19 amendments. Applicant may submit that subject matter in a preliminary amendment filed under section 1.121. In many cases, filing an amendment under section 1.121 is preferable since grammatical or idiomatic errors may be corrected." 1147 O.G. 29-40, at 36.

- a. ☐ are transmitted herewith.
 - b. ☐ have been transmitted
 - i. ☐ by the International Bureau.
Date of mailing of the amendment (from form PCT/1B/308): _____
 - ii. ☐ by applicant on (date) _____
Date
 - c. ☐ have not been transmitted as
 - i. ☐ applicant chose not to make amendments under PCT Article 19.
Date of mailing of Search Report (from form PCT/ISA/210.): _____
 - ii. ☐ the time limit for the submission of amendments has not yet expired.
The amendments or a statement that amendments have not been made will be transmitted before the expiration of the time limit under PCT Rule 46.1.
6. ☐ A translation of the amendments to the claims under PCT Article 19 (38 U.S.C. § 371(c)(3)):
- a. ☐ is transmitted herewith.
 - b. ☐ is not required as the amendments were made in the English language.
 - c. ☐ has not been transmitted for reasons indicated at point 5(c) above.
7. ☒ A copy of the international examination report (PCT/IPEA/409)
- ☒ is transmitted herewith.
 - ☐ is not required as the application was filed with the United States Receiving Office.
8. ☒ Annex(es) to the international preliminary examination report
- a. ☒ is/are transmitted herewith.
 - b. ☐ is/are not required as the application was filed with the United States Receiving Office.
9. ☒ A translation of the annexes to the international preliminary examination report
- a. ☐ is transmitted herewith.
 - b. ☒ is not required as the annexes are in the English language.

10/030749

10. ☒ An oath or declaration of the inventor (35 U.S.C. § 371(c)(4)) complying with 35 U.S.C. § 115

531 Rec'd PCT/PT

09 NOV 2001

- a. ☐ was previously submitted by applicant on _____
Date
- b. ☐ is submitted herewith, and such oath or declaration
- i. ☐ is attached to the application.
- ii. ☐ identifies the application and any amendments under PCT Article 19 that were transmitted as stated in points 3(b) or 3(c) and 5(b); and states that they were reviewed by the inventor as required by 37 C.F.R. § 1.70.
- c. ☒ will follow.

II. Other document(s) or information included:

11. ☒ An International Search Report (PCT/ISA/210) or Declaration under PCT Article 17(2)(a):

- a. ☐ is transmitted herewith.
- b. ☒ has been transmitted by the International Bureau.
Date of mailing (from form PCT/IB/308): 15 November 2000
- c. ☐ is not required, as the application was searched by the United States International Searching Authority.
- d. ☐ will be transmitted promptly upon request.
- e. ☐ has been submitted by applicant on _____
Date

12. ☒ An Information Disclosure Statement under 37 C.F.R. §§ 1.97 and 1.98:

- a. ☐ is transmitted herewith.
Also transmitted herewith is/are:
- ☐ Form PTO-1449 (PTO/SB/08A and 08B).
- ☐ Copies of citations listed.
- b. ☒ will be transmitted within THREE MONTHS of the date of submission of requirements under 35 U.S.C. § 371(c).
- c. ☐ was previously submitted by applicant on _____
Date

13. ☐ An assignment document is transmitted herewith for recording.

A separate ☐ "COVER SHEET FOR ASSIGNMENT (DOCUMENT) ACCOMPANYING NEW PATENT APPLICATION" or ☐ FORM PTO 1595 is also attached.

2005249-5440001

10/030749

531 Rec'd PCT/PTC 09 NOV 2001

14. ☒ Additional documents:

- a. ☒ Copy of request (PCT/RO/101)
- b. ☒ International Publication No. WO-00/69139
- i. ☐ Specification, claims and drawing
- ii. ☒ Front page only
- c. ☒ Preliminary amendment (37 C.F.R. § 1.121)
- d. ☐ Other

15. ☒ The above checked items are being transmitted

- a. ☒ before 30 months from any claimed priority date.
- b. ☐ after 30 months.

16. ☐ Certain requirements under 35 U.S.C. § 371 were previously submitted by the applicant on _____, namely:

AUTHORIZATION TO CHARGE ADDITIONAL FEES

WARNING: Accurately count claims, especially multiple dependant claims, to avoid unexpected high charges if extra claims are authorized.

NOTE: "A written request may be submitted in an application that is an authorization to treat any concurrent or future reply, requiring a petition for an extension of time under this paragraph for its timely submission, as incorporating a petition for extension of time for the appropriate length of time. An authorization to charge all required fees, fees under § 1.17, or all required extension of time fees will be treated as a constructive petition for an extension of time in any concurrent or future reply requiring a petition for an extension of time under this paragraph for its timely submission. Submission of the fee set forth in § 1.17(a) will also be treated as a constructive petition for an extension of time in any concurrent reply requiring a petition for an extension of time under this paragraph for its timely submission." 37 C.F.R. § 1.136(a)(3).

NOTE: "Amounts of twenty-five dollars or less will not be returned unless specifically requested within a reasonable time, nor will the payer be notified of such amounts; amounts over twenty-five dollars may be returned by check or, if requested, by credit to a deposit account." 37 C.F.R. § 1.26(a).

- ☒ The Commissioner is hereby authorized to charge the following additional fees that may be required by this paper and during the entire pendency of this application to Account No. 23-0442

- ☒ 37 C.F.R. § 1.492(a)(1), (2), (3), and (4) (filing fees)

WARNING: Because failure to pay the national fee within 30 months without extension (37 C.F.R. § 1.495(b)(2)) results in abandonment of the application, it would be best to always check the above box.

(Transmittal Letter to the United States Elected Office (EO/US) [13-18]—page 7 of 8)

10030749-0442

10/030749

09 NOV 2001

- ☐ 37 C.F.R. § 1.492(b), (c) and (d) (presubstantive claims)

NOTE: Because additional fees for excess or multiple dependent claims not paid on filing or on later presentation must only be paid or these claims cancelled by amendment prior to the expiration of the time period set for response by the PTO in any notice of fee deficiency (37 C.F.R. § 1.492(d)), it might be best not to authorize the PTO to charge additional claim fees, except possible when dealing with amendments after final action.

- ☐ 37 C.F.R. § 1.17 (application processing fees)
- ☐ 37 C.F.R. § 1.17(a)(1)-(5) (extension fees pursuant to § 1.136(a).
- ☐ 37 C.F.R. § 1.18 (issue fee at or before mailing of Notice of Allowance, pursuant to 37 C.F.R. § 1.311(b))

NOTE: Where an authorization to charge the issue fee to a deposit account has been filed before the mailing of a Notice of Allowance, the issue fee will be automatically charged to the deposit account at the time of mailing the notice of allowance. 37 C.F.R. § 1.311(b).

NOTE: 37 C.F.R. § 1.28(b) requires "Notification of any change in loss of entitlement to small entity status must be filed in the application . . . prior to paying, or at the time of paying . . . issue fee." From the wording of 37 C.F.R. § 1.28(b): (a) notification of change of status must be made even if the fee is paid as "other than a small entity" and (b) no notification is required if the change is to another small entity.

- ☐ 37 C.F.R. § 1.492(e) and (f) (surcharge fees for filing the declaration and/or filing an English translation of an International Application later than 30 months after the priority date).



SIGNATURE OF PRACTITIONER

Alfred A. Fressola

(type or print name of practitioner)

Ware, Fressola, Van Der Sluys & Adolphson LLP

755 Main Street, Building Five

P.O. Address

PO Box 224

Monroe, CT 06468

Reg. No.: 27,550

Tel. No.: (203) 261-1234

Customer No.: 004955

10030749-042902

10/030749

531 Rec'd PCT/

09 NOV 2001

PATENT
915.401

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In the matter of: Bergenwall et al)
Serial No:) Group Art Unit
Filed: Herewith) Examiner:
PCT INTERNATIONAL FILING NO. PCT/IB00/00706)
PCT INTERNATIONAL FILING DATE: May 8, 2000)
For: Header Compression)

ASSISTANT COMMISSIONER OF PATENTS
WASHINGTON, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Please preliminarily amend the above-referenced application as follows:

In the Specification:

On page 1, prior to line 2, please insert a new heading as follows:

--Technical Field--.

On page 1, prior to line 5, please insert a new heading as follows:

5 --Background of the Invention--.

On amended page 3, prior to line 15, please insert a new heading as follows:

--Summary of the Invention--.

Express Mail No. EV005523171 US

10030749.042902

Please replace paragraph beginning at line 5 of page 4, with the following rewritten paragraph:

--The method preferably comprises selecting one or more segment formats that include a greater amount of control data increasingly preferentially when the estimated quality decreases, and preferably *vice versa*. It is preferred that when the estimated quality decreases, a greater amount of error check and/or correction data is sent in comparison to the amount of message data that is sent, and preferably *vice versa*. The available segment formats suitably include a first format including a first amount of control data and a second format including a second amount of control data, the second amount being less than the first amount. The method may then comprise selecting the first format with increasing frequency when the indicated quality of the link decreases, and preferably *vice versa*.--

On amended page 6, prior to line 9, please insert a new heading as follows:

--Brief Description of the Drawings--

On amended page 6, prior to line 15, please insert a new heading as follows:

--Best Mode for Carrying Out the Invention--

Please replace paragraph beginning at line 15 of amended page 6, with the following rewritten paragraph:

--The telecommunications system of figure 1 comprises a cellular telephone system that is controlled by control apparatus indicated as 1. The control apparatus controls radio base stations 2, 3 which are capable of communicating with handset terminals 4, 5 by radio.

The control apparatus is linked to a public switched telephone network (PSTN) 6 and to packet-based networks 7 such as the internet. Terminals 8, 9 are linked directly to the networks 6, 7 respectively. Users of any of the terminals may communicate with the users of any of the other terminals by establishing a connection across the intervening equipment.--

5

In the Claims:

Claims 3, 4, 6, 7, 8, 9, 10, 11 and 13 have been amended as follows:

1 3. (Amended) A method as claimed in claim 1, wherein the available segment
2 formats include a first format including a first amount of control data and a second format
3 including a second amount of control data, the second amount being less than the first
4 amount, and wherein the method comprises selecting the first format with increasing
5 frequency when the indicated quality of the link decreases.

1 4. (Amended) A method as claimed in claim 1, wherein the data segments are
2 packets.

1 6. (Amended) A method as claimed in claim 5, wherein the available segment
2 formats include a first format including a first amount of control data and a second format
3 including a second amount of control data, the second amount being less than the first

amount, and wherein the method comprises selecting the first format with increasing frequency when the indicated quality of the link decreases, and further wherein the first format is a format having a non-compressed header and the second format is a format having a compressed header.

7. (Amended) A method as claimed in claim 1, wherein the quality of the data path is estimated by means of one or more of the following measures; signal to interference ratio, bit error rate, power loss over the path, required transmission power over the path, delay over the path.

8. (Amended) A method as claimed in claim 1, wherein the path includes a portion over which no bit error correction protocol is applied.

9. (Amended) A method as claimed in claim 1, wherein the path includes a portion constituted by a radio link.

10. (Amended) A method as claimed in claim 1, wherein the data segments are formed and transferred according to one or more of the following protocols; TCP, IP, UDP, RTP.

11. (Amended) A method as claimed in claim 1, wherein each packet includes message data representing at least part of the message.

13. (Amended) A method as claimed in claim 11, wherein the control data of each segment includes first control data for permitting control of the transmission and/or reception of the segment and second control data for permitting detection and/or correction of errors in the first control data.

In the Abstract:

After the claim pages, please insert the following page:

--Abstract of the Disclosure

A method for communicating a message over a data path by means of data transfer apparatus capable of transmitting the data over the data path, generating a representation of the data as received from the data path and generating an indication of the communication quality of the data path; the method comprising: forming a plurality of individual data segments together representing the message, the format of each data segment being selected from one of a plurality of available segment formats in dependence on the quality of the data path; transferring the segments over the data path by means of the data transfer apparatus; and combining the segments as received from the data transfer apparatus to form a representation of the message.--

REMARKS


This preliminary amendment is filed for the purpose of placing the application into standard U.S. format. Consideration and allowance of the claims is earnestly solicited.

Claims 3, 4, 6, 7, 8, 9, 10, 11 and 13 have been amended.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version with markings to show changes made."

Respectfully submitted,

Date: 8 Nov 2001



Alfred A. Fressola, Reg. No. 27,550
Ware, Fressola, Van Der Sluys
& Adolphson LLP
Bradford Green, Building Five
755 Main Street, PO Box 224
Monroe, CT 06468
(203) 261-1234

VERSION WITH MARKINGS TO SHOW CHANGES MADEIn the Specification:

Paragraph beginning at line 5 of page 4 has been amended as follows:

The method preferably comprises selecting one or more segment formats that include a greater amount of control data increasingly preferentially when the estimated quality decreases, and preferably *vice versa*. It is preferred that when the estimated quality decreases, a greater amount of error check and/or correction data is sent in comparison to the amount of message data that is sent, and preferably *vice versa*. The available segment formats suitably include a first format including a first amount of control data and a second format including a second amount of control data, the second amount being less than the first amount. The method may then comprise selecting the first format with increasing frequency when the indicated quality of the link decreases, and preferably *vice versa*.[]

Paragraph beginning at line 15 of amended page 6 has been amended as follows:

The telecommunications system of figure 1 comprises a cellular telephone system that is controlled by control apparatus indicated as 1. The control apparatus controls radio base stations 2, 3 which are capable of communicating with handset terminals 4, 5 by radio. The control apparatus is linked to a public [service] switched telephone network (PSTN) 6 and to packet-based networks 7 such as the internet. Terminals 8, 9 are linked directly to the networks 6, 7 respectively. Users of any of the terminals may communicate with the users of any of the other terminals by establishing a connection across the intervening equipment.

Claims 3, 4, 6, 7, 8, 9, 10, 11 and 13 have been amended as follows:

1 3. (Amended) A method as claimed in claim 1 [or 2], wherein the available
2 segment formats include a first format including a first amount of control data and a second
3 format including a second amount of control data, the second amount being less than the first
4 amount, and wherein the method comprises selecting the first format with increasing
5 frequency when the indicated quality of the link decreases.

1 4. (Amended) A method as claimed in [any of claims 1 to 3] claim 1, wherein
2 the data segments are packets.

1 6. (Amended) A method as claimed in claim 5, wherein the available segment
2 formats include a first format including a first amount of control data and a second format
3 including a second amount of control data, the second amount being less than the first
4 amount, and wherein the method comprises selecting the first format with increasing
5 frequency when the indicated quality of the link decreases [as dependent on claim 3], and
6 further wherein the first format is a format having a non-compressed header and the second
7 format is a format having a compressed header.

1 7. (Amended) A method as claimed in [any preceding claim] claim 1, wherein
2 the quality of the data path is estimated by means of one or more of the following measures;

3 signal to interference ratio, bit error rate, power loss over the path, required transmission
4 power over the path, delay over the path.

1 8. (Amended) A method as claimed in [any preceding claim] claim 1, wherein
2 the path includes a portion over which no bit error correction protocol is applied.

1 9. (Amended) A method as claimed in [any preceding claim] claim 1, wherein
2 the path includes a portion constituted by a radio link.

1 10. (Amended) A method as claimed in [any preceding claim] claim 1, wherein
2 the data segments are formed and transferred according to one or more of the following
3 protocols; TCP, IP, UDP, RTP.

1 11. (Amended) A method as claimed in [any of claims 1 to 10] claim 1, wherein
2 each packet includes message data representing at least part of the message.

1 13. (Amended) A method as claimed in claim 11 [or 12], wherein the control data
2 of each segment includes first control data for permitting control of the transmission and/or
3 reception of the segment and second control data for permitting detection and/or correction
4 of errors in the first control data.

HEADER COMPRESSION

This invention relates to the communication of data, and particularly to a method for communicating data in which the format of the data – for example the level of header compression – is dependant on the quality of the communications link.

A variety of protocols are available for the communication of a data message over a communications link. In numerous protocols the message is divided into packets at the transmitter end; the packets are conveyed individually over the communications link; and at the receiver end the packets are combined to re-form the message. Each packet normally comprises a payload, which represents the portion of the message that the packet carries, and control data, which are used in the communication procedure itself. The control data are normally in a contiguous block at the beginning of the packet (a header) but could be at the end of the packet (a trailer) or distributed through it. The functions of the control data can include:

1. indicating the source address of the packet,
2. indicating the destination address of the packet,
3. indicating the location of the payload's data in the message, and
4. providing error check or error correction information for the header, the packet or the message.

One example of a packet protocol is TCP/IP (transmission control protocol / internet protocol). In basic TCP/IP the transmitting unit gives each packet a 40 byte header which contains information for all the functions 1 to 4 above. As the packet passes over the communication link the destination address of the packet is used to route the packet to the receiving unit. At the receiving unit the error check information is used to check that the packet has been received intact; if an error is detected then the transmitting unit is requested to retransmit the packet. Then the receiving unit extracts the payload from each packet and combines the payloads in the order indicated by the location information in their respective headers, to re-form the message.

10030749-0429002

The basic 40 byte header represents a significant proportion of the bandwidth used for the transmission. To address this high overhead a mechanism [RFCs 1144, 2507, 2508, 2509] for compression of TCP/IP headers has been developed. Using this mechanism the TCP/IP header can be compressed from 40 to a minimum of 4 bytes. TCP/IP header compression [RFC1144] is today widely used in combination with PPP (point-to-point protocol) for dial-up links over modem and other low speed connections.

The header compression mechanism is based on the fact that most of the fields in the TCP and IP headers are constant or change very little during the transmission of a message. For example, the source address and destination address are the same for all the packets of the message. To exploit this the header compression mechanism operates by transmitting the whole header only once, in the first packet of the message, and after that only the parts that have changed. The compression mechanism can be enhanced by not transmitting changes in the header that are obvious for both transmitter and receiver. Similar mechanisms have been proposed for UDP/IP and RTP/UDP/IP.

EP 0 616 455 describes a computer network where messages are sent over the links between the computers in compressed, segmented form, the size of the segments being appropriate to the transmission characteristics of the link.

WO 96/21984 describes a packet radio system which encapsulates data packets of external packet data networks by PPP and passes them through one or more sub-networks to a point which supports the protocol of the encapsulated data packet. A PPP packet is compressed before the encapsulation of a special radio link protocol by removing therefrom the unnecessary control fields.

The TCP/IP header compression mechanism is an effective way to improve bandwidth efficiency for many point to point links, when the link is reliable and there are no errors. However, if the compressed headers are distorted due to errors in the transmission link then significant problems can arise. Because the

2A

compression mechanism operates by transmitting only the changes from one header to the next, if one header is received wrongly then that error propagates and affects the receiver's interpretation of succeeding compressed headers, destroying the integrity of those headers' packets. This means that those packets must to be re-transmitted. On a link in which there is a high BER (bit error rate), such as many cellular radio links, the bandwidth used to retransmit packets that have been wrongly received due to header compression can be greater than the bandwidth saved by sending the compressed headers.

There is provision for a gradual increase in the level of TCP/IP header compression on a link over time. Full headers are sent periodically, and the interval between the sending of a full header increases exponentially to an upper limit. (The upper limit exists so that the connection will eventually overcome even an undetected bit error in a compressed header). If an error is detected, using the received data at the TCP/IP protocol level, then the interval is reset to the minimum and then begins to increase again.

Some high BER links run an error-checking retransmission protocol under the TCP/IP protocol to ensure that the TCP/IP protocol receives data intact and free from bit errors. However, the presence of an underlying retransmission protocol cannot be guaranteed – for example, in the proposed standard for the transmission of packet data over third-generation (UMTS) cellular systems the use of a layer 2 retransmission protocol is still uncertain.

There is therefore a need for an improved method of header compression.

According to one aspect of the present invention there is provided a method for communicating a message over a data path, the method comprising: forming a plurality of individual data segments together representing the message, each data segment having control data; transferring the data segments over the data path; characterised in that the quality of the data path is estimated such that the format of each data segment being selected from one of a plurality of available segment formats in dependence on the quality of the data path and wherein the available segment formats differ in the amount of control data that they include.

Preferably the amount of control data is for example error check and/or correction data and/or data for other control purposes as set out above. There may be two or more available segment

formats. The segment formats may be of different lengths, or may all be the same length (in which case some of the segment formats preferably include more data representing at least part of the message than do others). The control data may permit the detection and/or correction of errors in a segment as received.

The method preferably comprises selecting one or more segment formats that include a greater amount of control data increasingly preferentially when the estimated quality decreases, and preferably *vice versa*. It is preferred that when the estimated quality decreases a greater amount of error check and/or correction data is sent in comparison to the amount of message data that is sent, and preferably *vice versa*. The available segment formats suitably include a first format including a first amount of control data and a second format including a second amount of control data, the second amount being less than the first amount. The method may then comprise selecting the first format with increasing frequency when the indicated quality of the link decreases, and preferably *vice versa*.

The data segments may be packets or other datagrams. The control data may suitably be comprised in a header and/or trailer of each packet. The said first format may be a format having a non-compressed header whilst the second format may be format having a compressed header.

The method comprises estimating the quality of the data path. The quality of the data path is preferably represented by the quality of communications over the path, or over another path that may be assumed to have similar quality characteristics to the path - for example a path sharing a communications link with the path but in the opposite direction or on a different channel. The quality of communications over the path may be represented by the quality of communications over a part of the path, preferably an error-prone part of the path such as a radio link.

The quality of the data path or a representative path may be estimated by any suitable measure, or by more than one measure. The quality of the data path or a representative path may be estimated by means of one or more of the following measures: signal to interference ratio, bit error rate, power loss over the path, required transmission power over the path, delay over the path. The quality of the data path may be estimated periodically. The quality of the data path is preferably estimated periodically so as to update the estimate of quality one or more times during the step of forming the plurality of individual data segments together representing the message

The path may include a portion over which no bit error correction protocol is applied, e.g. a radio link over which there is no layer 2 protocol. The path may include a portion constituted by a radio link, e.g. a satellite or cellular telephony link.

The data segments may be formed and/or transferred according to one or more of the following protocols: TCP, IP, UDP, RTP.

Each packet preferably includes message data representing at least part of the message. Each of the available segment formats may have the same capacity to carry message data.

The control data of each segment may include first control data (e.g. header data) for permitting detection and/or correction of errors in message data of the segment and/or for permitting control over the transmission and/or reception of the segment and second control data (e.g. header error check data) for permitting detection and/or correction of errors in the first control data. Preferably any available segment formats including greater amounts of first control data include greater amounts of second control data.

According to a second aspect of the present invention there is provided a communication system for communicating a message over a data path,

comprising: data forming apparatus for forming a plurality of individual data segments together representing the message, each data segment having control data; data transfer apparatus capable of transmitting the data segments over the data path; characterised in having: path quality estimation apparatus for estimating the quality of the path and in the data forming apparatus the format of each data segment being selected from one of a plurality of available segment formats in dependence on the quality of the data path wherein the available segment formats differ in the amount of control data that they include.

The present invention will now be described by way of example, with reference to the accompanying drawings, in which:

Figure 1 shows a schematic diagram of a telecommunications system;

Figure 2 shows a simplified protocol stack for transmission of data in the system of figure 1; and

Figure 3 shows the structure of data packets.

The telecommunications system of figure 1 comprises a cellular telephone system that is controlled by control apparatus indicated as 1. The control apparatus controls radio base stations 2, 3 which are capable of communicating with handset terminals 4, 5 by radio. The control apparatus is linked to a public service telephone network (PSTN) 6 and to packet-based networks 7 such as the internet. Terminals 8, 9 are linked directly to the networks 6, 7 respectively. Users of any of the terminals may communicate with the users of any of the other terminals by establishing a connection across the intervening equipment.

Figure 2 shows a simplified protocol stack for a data connection between terminal 4 and terminal 9 via base station 2. The data connection illustrated by figure 2 is the transmission of a message of data stored at the terminal 4 – for example a text message or data representing a photograph. To support this connection the TCP/IP protocol is run between the terminal 4 and the terminal 9; and below the TCP/IP protocol a layer 1 protocol is run between the terminal 4 and the base station 2. Accordingly, figure 1 shows that the terminal 4 includes TCP/IP

6A

processing apparatus 20 and layer 1 processing apparatus 21, the base station 2

10030749.042902

includes layer 1 processing apparatus 22 and the terminal 9 includes TCP/IP processing apparatus 23. The apparatus 20 and 21 could be embodied in a single DSP (digital signal processor). Any of the apparatus 20-23 could be embodied by dedicated hardware or constituted by software running on multi-purpose hardware. Layer 1 information may be exchanged between the terminal 4 and the base station 2 over more than one radio channel – for example, traffic information may be sent over a traffic channel and control information over a control channel.

In this example system the layer 1 protocol governs the operation of the air interface between the terminal 4 and the base station 2. At the transmitter end the layer 1 protocol transforms the TCP/IP data (or any other form of data) processed by layer 2 into layer 1 data for transmission over the air interface. The processing may, for instance, involve breaking the TCP/IP packets down into chunks of a suitable size to be sent in frames of a standard size over the air interface. At the receiver end the layer 2 protocol reassembles the TCP/IP packets (or other data) to form the layer 2 output. If the link between transmitter and receiver were perfect then the layer 1 output would be a perfect copy of the input to layer 1 from the TCP/IP layer processed by layer 2 at the transmitter end. However, bit errors can arise over the air interface, and a layer 1 protocol does not generally perform error checking, so the layer 1 output may differ from the layer 1 input. In addition to its function of transmitting the message data, the layer 2 protocol exchanges layer 2 control data between the units at its ends. This data is used to take care of air interface issues such as power control and handover from one base station to another. In many systems the apparatus executing the layer 1 protocol generates or controls the generation of and generally has access to information on a number of factors that are indicative of the quality of the link between its ends, such as signal to interference ratio (SIR), the power with which one of the end radio units of the link receives the other, the attenuation over the link and the delay over the link, each in one or both of the directions over the link. This information may be collected at both ends of the link and exchanged between the ends of the link, so, for example, the terminal 4 maybe made aware

10030749.042902

by the base station 2 of the quality measured by the base station of received signals on the downlink from the terminal to the base station and *vice versa*.

The message data that is to be transmitted from the terminal 4 could be generated in any available way, for instance it could be a text file (encoded e.g. according to the ASCII format) or data representing a picture (encoded e.g. according to a JPEG format), a video (encoded e.g. according to an MPEG format) or speech (encoded e.g. according to the H.323 format for voice over IP).

In summary, the process for transmitting message data at 20 in terminal 4 to the terminal 9 is as follows:

1. the message data is identified or formed at the terminal 4;
2. the message data is transformed according to the TCP/IP protocol to form TCP/IP data;
3. the TCP/IP data is transformed according to the level 1 protocol to form level 1 data;
4. the level 1 data is communicated by radio to the base station 2 according to the level 1 protocol (bit errors may be introduced in this step);
5. the received level 1 data is transformed at the base station 2 to recover a representation of the TCP/IP data at the terminal 4;
6. the representative TCP/IP data is communicated over the network 7 to the terminal 9 according to the TCP/IP protocol;
7. the representative TCP/IP data is transformed at the terminal 9 according to the TCP/IP protocol at 20 is transformed using the TCP/IP protocol to recover a representation of the message data.

It should be noted that there may be other layers in the protocol stack, and that the functions provided within the protocol stack may be divided differently between the layers that are present. For example, the protocol stack may include a layer 2 protocol which may or may not provide error checking functions; header compression functions could be provided by a layer 2 protocol, if present; division

of data into frames could happen at the layer 2 stage. TCP may represent a layer 3 protocol and IP a layer 4 protocol.

The error check information in the headers of the TCP/IP packets can be used to check whether each TCP/IP packet has been received correctly at the terminal 9. If an error is detected (which would probably have arisen at step 4) then the terminal 9 can request retransmission of individual packets. In this way the message data can be recreated accurately at the terminal 9. If conventional TCP/IP header compression is used then when the probability of error on the radio link at step 4 is low there may be a saving in bandwidth. However, if the probability of error is high then the overhead due to retransmission of packets is likely to outweigh the saving from transmitting shorter headers.

The system of figure 1 includes a link 10 from the layer 1 apparatus 21 via the control processor 24 of terminal 4 to the TCP/IP apparatus 20. Using this link the information known to the layer 1 apparatus on the quality of the radio link between terminal 4 and the base station 2 can be communicated to the TCP/IP apparatus. Using the methods described below the TCP/IP apparatus can then adapt the format of the TCP/IP packets it generates, and in particular the level of header compression, in dependence on the quality of the link. The TCP/IP apparatus may receive the link quality information and/or additional link quality information from another source – for instance an additional unit in the terminal 4 that estimates link quality. The quality estimation, e.g. an error rate, could be obtained directly from the radio network subsystem (in a cellular implementation) or by directly monitoring the error rate for the compressed headers or their packets.

The decision of the TCP/IP unit 20 on the level of header compression to be used could be based on one or more of any available measures of link quality, such as SIR, an error rate (e.g. bit error rate, byte error rate, header error rate, packet error rate), requested transmit power, estimated path loss, estimated delay over the path. The measures used are preferably measures of the quality of the link in the direction in which the data generated by the TCP/IP unit is to be sent, but in

10030749.042902

many situations measures of the quality of the link in the opposite direction will be to some extent representative of link quality in the transmission direction and could therefore be used too or instead. Where more than one measure is used then an algorithm to effectively combine the used measures could be employed. Other factors may also be taken into account in deciding on the level of header compression – for instance user-generated information for controlling the desired header compression performance, or information from the network on traffic intensity. By using this information during the course of a connection and/or during the transmission of a message the level of header compression can be dynamically adjusted to suit the level of header compression to the probability of error.

The TCP/IP unit 20 includes apparatus (in dedicated hardware or in software) for executing an algorithm to control the generation of TCP/IP packets taking into account one or more measures of link quality. If the probability of error is higher then increased amounts of header information can be sent; if the probability of error is lower then reduced amounts of header information can be sent. The variation in the amount of header information may be achieved by dynamically adjusting the length of headers from between successive packets.

Some strategies for adjusting header lengths will now be described. One possibility is to adjust the frequency with which full headers or compressed headers are sent in dependence on the estimated link quality. Instead of the predefined exponentially growing interval of the prior art, the interval (i.e. the number of packets sent with compressed headers) between packets with full headers could vary depending on the estimated link quality, from zero or one upwards, optionally to a predefined upper limit. If every second header is sent uncompressed (equivalent to an interval of one) the connection still benefits somewhat from the header compression but an error in a header will at most affect only the next compressed header. There could be no upper limit on the interval - if the link were of excellent quality - so the interval could be anything between infinity (never sending uncompressed headers) and zero (always

sending uncompressed headers). Figures 3a and 3b show two different situations, with reference numeral 30 denoting a packet, reference numeral 31 denoting a compressed header and reference numeral 32 denoting an uncompressed header. Figure 3a shows a situation of high link quality. Figure 3b shows a situation of low link quality.

The uncompressed header interval can be either one value common for all communications over a link or different for different channels or connections (e.g. TCP connections) over a link. The value could be the same or different for the two directions over a link. The decision on an uncompressed header interval could be made by both terminating TCP units or by just one (preferably the one that is solely or principally transmitting data that will be affected by the decision).

In cellular systems the variable interval header compression may be implemented between a mobile station and the corresponding node in the network (e.g. in the GPRS at the SGSN).

It may also be advantageous to implement header error correction (HEC) over the TCP link, whereby bits are transmitted so that errors in a header itself can be detected and/or corrected, with a probability of detection or correction depending on the number of HEC bits that are used relative to the size of the header. If a packet's header is not received correctly then that whole packet may have to be discarded and/or retransmitted. If a means of header error correction were available then it may be possible to correct the header and thereby avoid the need to discard or retransmit the packet. Relatively few HEC bits are needed to give a good probability of correcting errors in a compressed header. Therefore, it may be found efficient to use an additional error correction code covering compressed headers so that as many header bit errors as possible can be corrected. Depending on the size of the compressed header and the environment's BER the size (number of bits) of the HEC field may usefully be adjustable in order to keep the error correction as optimal as possible. This can be achieved by using potentially reserved bits of a packet (preferably the packet's first bits) to convey

the size of the HEC field. The extra HEC bits themselves will add some length to the compressed header and it is thus feasible to keep the HEC relatively small. On the other hand it is advantageous to arrange that the header can be corrected in case of an error. Figure 3c illustrates a packet 30 with compressed header 31 and a HEC field 33, the bits 34 indicating the HEC field length. It is preferred that the HEC field length should be dynamically changeable and adaptive to the quality of the connection. The HEC size could vary between no HEC at all to a predefined upper limit. The HEC size could be either one value common for all communications over a link or different for different channels or connections (e.g. TCP connections) over a link. The size could be the same or different for the two directions over a link.

The methods described above may be applied to other protocols than TCP. In general, they may be overlain on to any protocol that involves the transmission of discrete amounts of data (e.g. packets or other datagrams), of fixed or variable lengths, provided the provision of the features described above does not conflict technically essential features of the protocol. Examples of other protocols on to which it could be overlain include UDP/IP and RTP/UDP/IP.

The methods described above may be applied to a variety of communications systems, including cellular, satellite and ground-based links.

The present invention is not limited to the examples described above.

The applicant draws attention to the fact that the present invention may include any feature or combination of features disclosed herein either implicitly or explicitly or any generalisation thereof, without limitation to the scope of any of the present claims. In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention.

CLAIMS

1. A method for communicating a message over a data path, the method comprising:

forming a plurality of individual data segments together representing the message, each data segment having control data;

transferring the data segments over the data path;

characterised in that the quality of the data path is estimated and the format of each data segment is selected from one of a plurality of available segment formats in dependence on the quality of the data path and wherein the available segment formats differ in the amount of control data that they include.

2. A method as claimed in claim 1, wherein the method comprises selecting one or more segment formats that include a greater amount of control data increasingly when the indicated quality decreases.

3. A method as claimed in claim 1 or 2, wherein the available segment formats include a first format including a first amount of control data and a second format including a second amount of control data, the second amount being less than the first amount, and wherein the method comprises selecting the first format with increasing frequency when the indicated quality of the link decreases.

4. A method as claimed in any of claims 1 to 3, wherein the data segments are packets.

5. A method as claimed in claim 4, wherein the control data is comprised in a header and/or trailer of each packet.

6. A method as claimed in claim 5 as dependent on claim 3, wherein the first format is a format having a non-compressed header and the second format is a format having a compressed header.

7. A method as claimed in any preceding claim, wherein the quality of the data path is estimated by means of one or more of the following measures: signal to interference ratio, bit error rate, power loss over the path, required transmission power over the path, delay over the path.

8. A method as claimed in any preceding claim, wherein the path includes a portion over which no bit error correction protocol is applied.

9. A method as claimed in any preceding claim, wherein the path includes a portion constituted by a radio link.

10. A method as claimed in any preceding claim, wherein the data segments are formed and transferred according to one or more of the following protocols: TCP, IP, UDP, RTP.

11. A method as claimed in any of claims 1 to 10, wherein each packet includes message data representing at least part of the message.

12. A method as claimed in claim 11, wherein the available segment formats do not differ in their ability to comprise message data.

13. A method as claimed in claim 11 or 12, wherein the control data of each segment includes first control data for permitting control of the transmission and/or reception of the segment and second control data for permitting detection and/or correction of errors in the first control data.

14. A method as claimed in claim 13, wherein the available segment formats including greater amounts of first control data include greater amounts of second control data.

15. A communication system for communicating a message over a data path, comprising:

data forming apparatus for forming a plurality of individual data segments together representing the message, each data segment having control data;

data transfer apparatus capable of transmitting the data segments over the data path;

characterised in having:

path quality estimation apparatus for estimating the quality of the path and in the data forming apparatus the format of each data segment being selected from one of a plurality of available segment formats in dependence on the quality of the data path wherein the available segment formats differ in the amount of control data that they include.




FIG. 1




FIG. 2

2 / 2




FIG. 3a




FIG. 3b




FIG. 3c

COMBINED DECLARATION AND POWER OF ATTORNEY

(Docket Number)

As a below named inventor, I hereby declare that:

915.401

- my residence, post office address and citizenship are as stated below next to my name;
- I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **HEADER COMPRESSION**
- the specification of which is attached hereto unless the following box is checked: ☒. If the box is checked,

the application was filed on November 9, 2001
as U.S. Application Number 10/030,749
or PCT International Application Number PCT/IB00/00706
and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application			Priority Not Claimed
9910797.1 (Application Number)	Great Britain (Country)	10/05/99 (Day/Month/Year Filed)	<input type="checkbox"/>
9911550.3 (Application Number)	Great Britain (Country)	18/05/99 (Day/Month/Year Filed)	<input type="checkbox"/>

To the extent permitted by rule or law, I hereby incorporate by reference the Prior Foreign Application(s) listed above.

I hereby claim the benefits under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

(Provisional Application Number)	(Day/Month/Year Filed)
(Provisional Application Number)	(Day/Month/Year Filed)

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose information which is material to patentability, as defined in 37 CFR §1.56, which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application Number)	(Day/Month/Year Filed)	(Status--patented, pending, abandoned)
(Application Number)	(Day/Month/Year Filed)	(Status--patented, pending, abandoned)


10030749.042902

The undersigned hereby authorizes the U.S. firm of Ware, Fressola, Van Der Sluys & Adolphson LLP to accept and follow instructions from the English firm of Page White & Farrer as to any action to be taken in the U.S. Patent and Trademark Office regarding this application without direct communication between the U.S. firm and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. firm will be so notified by the undersigned.

I hereby appoint the attorney(s) and/or agent(s) assigned to the customer number listed below, as may from time to time be amended, belonging to the U.S. firm of Ware, Fressola, Van Der Sluys & Adolphson LLP, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Customer Number


4955



Address all telephone calls to: Ware, Fressola, Van Der Sluys & Adolphson LLP at (203) 261-1234. Address all correspondence to: Alfred A. Fressola

Customer Number

4955



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1-00 Martin BERGENWALL Full name of sole or first inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)	
	8.3. 2002 Date
02230 Espoo, Finland Residence	Finnish Citizenship FIX
Post Office Address: Kalastajankuja 1 A6, 02230 Espoo, Finland	

2-00 Patrik FLYKT Full name of second inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)	
	6.3. 2002 Date
00640 Helsinki, Finland Residence	Finnish Citizenship FIX
Post Office Address: Hirsipadontie 7 K 97, 00640 Helsinki, Finland	

Full name of third inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)	
Inventor's Signature	Date
Residence	Citizenship
Post Office Address:	

☐ Additional inventors are being named on separately numbered sheets attached hereto.

10030749 04955